

RECEIVED  
CENTRAL FAX CENTERAMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

JAN 27 2005

AMENDMENTS TO THE CLAIMS

This listing of the claims replaces all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

1. [CANCELLED]
2. [PREVIOUSLY AMENDED] A method as claimed in claim 70, wherein the step of obtaining a class ID respecting the optical fiber medium comprises a step of receiving a fiber ID respecting the optical fiber medium.
3. [ORIGINAL] A method as claimed in claim 2, wherein the fiber ID is manually entered into the optical communications system.
4. [ORIGINAL] A method as claimed in claim 2, wherein the step of receiving a fiber ID comprises the steps of: probing the optical fiber medium for the presence of a predetermined marking containing information of the fiber ID; and if a marking is detected, reading information of the fiber ID from the marking.
5. [ORIGINAL] A method as claimed in claim 4, wherein the predetermined marking is a Bragg grating.
6. [ORIGINAL] A method as claimed in claim 2, further comprising a step of using the fiber ID to query a cross-reference table comprising a list of fiber ID's and a class ID associated with each fiber ID, to obtain the class ID respecting the optical fiber medium.
7. [PREVIOUSLY AMENDED] A method as claimed in claim 70, wherein the step of obtaining a class ID comprises the steps of:

## AMENDMENT UNDER 37 CFR § 1.111

Serial No. 10/625,696

discovering a value of at least one fiber transmission property of the optical fiber medium;

providing a class definition table comprising a plurality of class definitions, each class definition including at least:

a respective class ID; and

at least one corresponding characteristic transmission property value;

selecting a class ID from the class definition table based on a closest match between corresponding ones of the at least one fiber transmission property value and the at least one characteristic transmission property value.

8. [ORIGINAL] A method as claimed in claim 7, wherein each characteristic transmission property value comprises a respective nominal value, and an allowable tolerance defining a value range of the characteristic transmission property.
9. [ORIGINAL] A method as claimed in claim 8, further comprising a step of raising an alarm if any one fiber transmission property value does not lay within the value range of the corresponding characteristic transmission property, for any of the plurality of class definitions of the class definition table.
10. [ORIGINAL] A method as claimed in claim 7, wherein the step of obtaining a value of at least one fiber transmission property comprises a step of testing the optical fiber link in situ.
11. [ORIGINAL] A method as claimed in claim 7, wherein the step of obtaining a value of at least one fiber transmission property comprises a step of testing the optical fiber link prior to installation.
12. [ORIGINAL] A method as claimed in claim 7, wherein the step of obtaining a value of at least one fiber transmission property comprises obtaining a respective value of any one or more of: a total optical signal dispersion; a zero dispersion wavelength; an

## AMENDMENT UNDER 37 CFR § 1.111

Serial No. 10/625,696

- average optical signal attenuation; a length of the fiber; a total dispersion per unit length of the fiber; and an average attenuation per unit length of the fiber.
13. [ORIGINAL] A method as claimed in claim 12, wherein the at least one characteristic transmission property value comprises a respective value of any one or more of: the zero dispersion wavelength; the total dispersion per unit length of the fiber; and the average attenuation per unit length of the fiber.
14. [ORIGINAL] A method as claimed in claim 13, wherein the at least one characteristic transmission property value comprises a respective value of each one of the zero dispersion wavelength and the total dispersion per unit length of the fiber.
15. [ORIGINAL] A method as claimed in claim 7, wherein the step of selecting a class ID comprises the steps of:  
comparing each respective fiber transmission property value to a corresponding characteristic transmission property value within each class definition of the class definition table; and  
selecting the class ID of a one of the plurality of class definitions for which each characteristic transmission property value most closely matches a corresponding fiber transmission property value.
16. [PREVIOUSLY AMENDED] A method as claimed in claim 71, wherein the step of obtaining a respective optimum setting of each system parameter comprises a step of searching a system table comprising a plurality of system definitions, each system definition including a respective class ID and a corresponding optimum setting for each parameter.
17. [ORIGINAL] A method as claimed in claim 16, wherein all of the system definitions of the system table pertain to a predetermined set of one or more related optical communications systems.

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

18. [ORIGINAL] A method as claimed in claim 16, wherein the one or more system parameters comprises any one or more of: a transmission wavelength; a signal power; and a received signal detection threshold.
19. [ORIGINAL] A method as claimed in claim 18, wherein the step of adjusting a respective value of each system parameter comprises a step of adjusting a transmission wavelength of one or more lasers of the optical communications system.
20. [ORIGINAL] A method as claimed in claim 19, wherein the transmission wavelength of each laser is adjusted independently.
21. [ORIGINAL] A method as claimed in claim 19, wherein the transmission wavelength is adjusted by tuning.
22. [ORIGINAL] A method as claimed in claim 19, wherein the transmission wavelength is adjusted by means of one or more filters.
23. [ORIGINAL] A method as claimed in claim 18, wherein the step of adjusting a respective value of each system parameter comprises a step of adjusting a signal power of one or more lasers of the optical communications system.
24. [ORIGINAL] A method as claimed in claim 23, wherein the signal power of each laser is adjusted independently.
25. [ORIGINAL] A method as claimed in claim 18, wherein the step of adjusting a respective value of each system parameter comprises a step of adjusting a detection threshold of one or more optical signal detectors of the optical communications system.
26. [ORIGINAL] A method as claimed in claim 23, wherein the detection threshold of each optical signal detector is adjusted independently.

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

27. [CANCELLED]
28. [PREVIOUSLY AMENDED] An apparatus as claimed in claim 73, wherein the means for obtaining a class ID respecting the optical fiber medium comprises means for receiving a fiber ID respecting the optical fiber medium.
29. [ORIGINAL] An apparatus as claimed in claim 28, wherein the fiber ID is manually entered into the optical communications system.
30. [ORIGINAL] An apparatus as claimed in claim 28, wherein the means for receiving a fiber ID comprises means for: probing the optical fiber medium for the presence of a predetermined marking containing information of the fiber ID; and if a marking is detected, reading information of the fiber ID from the marking.
31. [ORIGINAL] An apparatus as claimed in claim 30, wherein the predetermined marking is a Bragg grating.
32. [ORIGINAL] An apparatus as claimed in claim 28, further comprising:  
a cross-reference table comprising a list of fiber ID's and a class ID associated with each fiber ID; and  
means for using the fiber ID to obtain the class ID by querying the cross-reference table.
33. [PREVIOUSLY AMENDED] An apparatus as claimed in claim 73, wherein the means for obtaining a class ID comprises:  
means for discovering a value of at least one fiber transmission property of the optical fiber link;  
a class definition table comprising a plurality of class definitions, each class definition including at least:  
a respective class ID; and

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

at least one corresponding characteristic transmission property value; and

means for selecting a class ID from the class definition table based on a closest match between corresponding ones of the at least one fiber transmission property value and the at least one characteristic transmission property value.

34. [ORIGINAL] An apparatus as claimed in claim 33, wherein each characteristic transmission property value comprises a respective nominal value, and an allowable tolerance defining a value range of the characteristic transmission property.
35. [ORIGINAL] An apparatus as claimed in claim 34, further comprising means for raising an alarm if any one fiber transmission property value does not lay within the value range of the corresponding characteristic transmission property, for any of the plurality of class definitions of the class definition table.
36. [ORIGINAL] An apparatus as claimed in claim 33, wherein the means for discovering a value of at least one fiber transmission property comprises a step of testing the optical fiber link in situ.
37. [ORIGINAL] An apparatus as claimed in claim 33, wherein the means for discovering a value of at least one fiber transmission property comprises means for discovering a respective value of any one or more of: a total optical signal dispersion; a zero dispersion wavelength; an average optical signal attenuation; a length of the fiber; a total dispersion per unit length of the fiber; and an average attenuation per unit length of the fiber.
38. [ORIGINAL] An apparatus as claimed in claim 37, wherein the at least one characteristic transmission property value comprises a respective value of any one or more of: the zero dispersion wavelength; the total dispersion per unit length of the fiber; and the average attenuation per unit length of the fiber.

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

39. [ORIGINAL] An apparatus as claimed in claim 38, wherein the at least one characteristic transmission property value comprises a respective value of each one of the zero dispersion wavelength and the total dispersion per unit length of the fiber.
40. [ORIGINAL] An apparatus as claimed in claim 33, wherein the means for selecting a class ID comprises:
- means for comparing each respective fiber transmission property value to a corresponding characteristic transmission property value within each class definition of the class definition table; and
- means for selecting the class ID of a one of the plurality of class definitions for which each characteristic transmission property value most closely matches a corresponding fiber transmission property value.
41. [PREVIOUSLY AMENDED] An apparatus as claimed in claim 74, wherein the means for obtaining a respective optimum setting of each parameter comprises means for searching a system table comprising a plurality of system definitions, each system definition including a respective class ID and a corresponding optimum setting for each parameter.
42. [ORIGINAL] An apparatus as claimed in claim 41, wherein each of the system definitions of the system table pertain to a predetermined set of one or more related optical communications systems.
43. [ORIGINAL] An apparatus as claimed in claim 41, wherein the one or more parameters comprises any one or more of: a transmission wavelength; a signal power; and a signal detection threshold.
44. [ORIGINAL] An apparatus as claimed in claim 43, wherein the means for adjusting a respective value of each parameter comprises means for adjusting a transmission wavelength of one or more lasers of the optical communications system.

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

45. [ORIGINAL] An apparatus as claimed in claim 44, wherein the means for adjusting a transmission wavelength of each laser is adapted to adjust each laser independently.
46. [ORIGINAL] An apparatus as claimed in claim 44, wherein the means for adjusting a transmission wavelength of each laser is adapted to adjust each laser by tuning.
47. [ORIGINAL] An apparatus as claimed in claim 43, wherein the means for adjusting a respective value of each system parameter comprises means for adjusting a signal power of one or more lasers of the optical communications system.
48. [ORIGINAL] An apparatus as claimed in claim 47, wherein the means for adjusting the signal power of each laser is adapted to adjust the signal power of each laser independently.
49. [ORIGINAL] An apparatus as claimed in claim 43, wherein the means for adjusting a respective value of each system parameter comprises means for adjusting a detection threshold of one or more optical signal detectors of the optical communications system.
50. [ORIGINAL] An apparatus as claimed in claim 49, wherein the means for adjusting the detection threshold of each optical signal detector is adapted to adjust the detection threshold of each optical signal detector independently.
51. [CANCELED]
52. [CANCELED]
53. [PREVIOUSLY AMENDED] A system as claimed in claim 76, wherein the class ID comprises a fiber ID respecting the optical fiber medium.
54. [ORIGINAL] A system as claimed in claim 53, wherein the fiber ID is manually entered into the optical communications system.

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

55. [AMENDED] A system as claimed in claim 53, wherein the controller is adapted to: control the transceiver to probe the optical fiber medium for the presence of a predetermined marking containing information of the fiber ID; and if a marking is detected, read information of the fiber ID from the marking.
56. [ORIGINAL] An apparatus as claimed in claim 55, wherein the predetermined marking is a Bragg grating.
57. [ORIGINAL] A system as claimed in claim 53, wherein the controller is further adapted to use the fiber ID to query a cross-reference table comprising a list of fiber ID's and a class ID associated with each fiber ID, to obtain the class ID respecting the optical fiber medium.
58. [CURRENTLY AMENDED] A system as claimed in claim 6875, wherein the controller is adapted to obtain a class ID by:  
discovering a value of at least one fiber transmission property of the optical fiber medium;  
searching a class definition table comprising a plurality of class definitions, each class definition including at least:  
a respective class ID; and  
at least one corresponding characteristic transmission property value; and  
selecting a class ID from the class definition table based on a closest match between corresponding ones of the at least one fiber transmission property value and the at least one characteristic transmission property value.
59. [ORIGINAL] A system as claimed in claim 58, wherein each characteristic transmission property value comprises a respective nominal value, and an allowable tolerance defining a value range of the characteristic transmission property.

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

60. [ORIGINAL] A system as claimed in claim 59, wherein the controller is further adapted to raise an alarm if any one fiber transmission property value does not lay within the value range of the corresponding characteristic transmission property, for any of the plurality of class definitions of the class definition table.
61. [ORIGINAL] A system as claimed in claim 58, wherein the at least one fiber transmission property comprises any one or more of: a total optical signal dispersion; a zero dispersion wavelength; an average optical signal attenuation; a length of the fiber; a total dispersion per unit length of the fiber; and an average attenuation per unit length of the fiber.
62. [ORIGINAL] A system as claimed in claim 61, wherein the at least one characteristic transmission property value comprises a respective value of any one or more of: the zero dispersion wavelength; the total dispersion per unit length of the fiber; and the average attenuation per unit length of the fiber.
63. [ORIGINAL] A system as claimed in claim 62, wherein the at least one characteristic transmission property value comprises a respective value of each one of the zero dispersion wavelength and the total dispersion per unit length of the fiber.
64. [PREVIOUSLY AMENDED] A system as claimed in claim 76, wherein the controller is adapted to select a class ID by:  
comparing each respective fiber transmission property value to a corresponding characteristic transmission property value within each class definition of the class definition table; and  
selecting the class ID of a one of the plurality of class definitions for which each characteristic transmission property value most closely matches a corresponding fiber transmission property value.
65. [PREVIOUSLY AMENDED] A system as claimed in claim 77, wherein the controller is adapted to obtain a respective optimum setting of each system parameter

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

by searching a system table comprising a plurality of system definitions, each system definition including a respective class ID and a corresponding optimum setting for each system parameter.

66. [ORIGINAL] A system as claimed in claim 65, wherein all of the system definitions of the system table pertain to a predetermined set of one or more related optical communications systems.
67. [PREVIOUSLY AMENDED] A system as claimed in claim 65, wherein the one or more system parameters comprises any one or more of: a transmission wavelength; a signal power; and a received signal detection threshold.
68. [CANCELLED]
69. [PREVIOUSLY PRESENTED] A method of optimizing a system parameter of an optical communications system adapted for connection to an optical fiber medium of an optical communications network; the method comprising steps of:  
obtaining information identifying the optical fiber medium; and  
adjusting a respective value of the system parameter in accordance with the obtained information.
70. [PREVIOUSLY PRESENTED] A method as claimed in claim 69, wherein the step of obtaining information identifying the optical fiber medium comprises a step of obtaining a class ID respecting the optical fiber medium.
71. [PREVIOUSLY PRESENTED] A method as claimed in claim 69, wherein the step of adjusting a respective value of the system parameter comprises steps of:  
obtaining a respective optimum setting of a system parameter on a basis of the obtained information; and

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

adjusting the respective value of the system parameter in accordance with the obtained optimum setting.

72. [PREVIOUSLY PRESENTED] An apparatus for optimizing system parameters of an optical communications system adapted for connection to an optical fiber medium of an optical communications network, the apparatus comprising:  
means for obtaining information identifying the optical fiber medium; and  
means for adjusting a respective value of the system parameter in accordance with the obtained information.
73. [PREVIOUSLY PRESENTED] An apparatus as claimed in claim 72, wherein the means for obtaining information identifying the optical fiber medium comprises means for obtaining a class ID respecting the optical fiber medium.
74. [PREVIOUSLY PRESENTED] An apparatus as claimed in claim 72, wherein the means for adjusting a respective value of the system parameter comprises:  
means for obtaining a respective optimum setting of a system parameter on a basis of the obtained information; and  
means for adjusting a respective value of the system parameter in accordance with the obtained optimum setting.
75. [PREVIOUSLY PRESENTED] An optical communications system adapted for connection to an optical fiber medium of an optical communications network, the optical communications system comprising:  
a transceiver including a port connected for bi-directional communications through the optical fiber medium;  
a controller unit for controlling operation of the optical communications system, the controller unit being adapted to:  
obtain information identifying the optical fiber medium; and

AMENDMENT UNDER 37 CFR § 1.111  
Serial No. 10/625,696

adjust a respective value of the system parameter in accordance with the obtained information.

76. [CURRENTLY AMENDED] A system as claimed in claim 75, wherein the controller unit is adapted to obtain the information identifying the optical fiber medium by obtaining a class ID respecting the optical fiber medium.
77. [PREVIOUSLY PRESENTED] A system as claimed in claim 75, wherein controller unit is adapted to adjust the respective value of the system parameter by:  
obtaining a respective optimum setting of a system parameter on a basis of the obtained information; and  
adjusting a respective value of the system parameter in accordance with the obtained optimum setting.